

## SPECIFICATION OF MAHAFIX RED DS-HR

PRODUCT DESCRIPTION	
<b>Brand Name</b>	Mahafix Red DS-HR
<b>C.I. Name</b>	N/A
<b>Substantivity</b>	High
<b>Solubility at 30°C</b>	150
<b>Dischargeability</b>	Medium

FASTNESS PROPERTIES	
<b>Dyeing Depth (%)</b>	3.0
<b>Neutral</b>	2-3
<b>Alkaline</b>	2-3
<b>Light</b>	4-5

1%	4%

SUITABILITY	
<b>Effect of Metal (Cu++)</b>	4BD
<b>Effect of Metal (Fe++)</b>	4-5
<b>Washing (Alteration)</b>	4-5
<b>Washing (Staining)</b>	4-5
<b>Chlorinated Water</b>	4-5

STANDARD PACKAGING	
<b>HDPE Bags</b>	25 Kgs
<b>Carton Box</b>	25 Kgs

Our product specific end application information are based upon our current knowledge. They are presented without any representation or warranty concerning the suitability, performance or correctness of the product for a particular application or use. Significant variations can occur between test results and results obtained in actual use. We strongly advise that the customer test the product in the specific intended application under conditions expected during use.

**FOR, MAHAVIR INDUSTRIES**



**PARTNER**

### CERTIFICATIONS



REGISTERED OFFICE: 1007-1008, DEV ATELIER COMPLEX, NR. SEEMA HALL, PRAHLADNAGAR ROAD, SATELLITE, AHMEDABAD - 380015, GUJARAT INDIA.

FACTORY UNIT-1 : C-1/58 PHASE-2 GIDC ESTATE, VATVA - AHMEDABAD - 382445, GUJARAT INDIA. UNIT-2 : C1/5639 PHASE-2 GIDC, ESTATE, VATVA-AHMEDABAD - 382445 GUJARAT INDIA