

SPECIFICATION OF MAHASOL ORANGE 6063

PRODUCT DESCRIPTION	
Brand Name	Mahasol Orange 6063
C.I. Name	Solvent Orange 63
C.I. No.	68550
CAS Registry No.	16294-75-0
EU No.	240-385-4
Melting Point (°C)	320°C
Chemical Formula	C ₂₃ H ₁₂ OS
Density (g/cm³)	1.49
Heat Resistance in PS, °C	300
Light Fastness in PS	8
Degree of Pigmentation	0.05% Dyes+0.1% Titanium Dioxide

SOLUBILITY AT 20°C	
Acetone	1.0
Butyl Acetate	1.0
Methyl benzene	0.3
Dichloromethane	0.5
Ethyl Alcohol	0.5

TINT TONE	MASS TONE

APPLICATION
Solvent Orange 63 is used for coloring for plastics, PS, ABS, PMMA, PC, PET, polymer, fiber & recommended for polyester fiber and PA6 fiber, limited use in PA66 fiber.

STANDARD PACKAGING	
HDPE Bags	25 Kgs
Carton Box	25 Kgs

Our product specific end application information are based upon our current knowledge. They are presented without any representation or warranty concerning the suitability, performance or correctness of the product for a particular application or use. Significant variations can occur between test results and results obtained in actual use. We strongly advise that the customer test the product in the specific intended application under conditions expected during use.

FOR, MAHAVIR INDUSTRIES




PARTNER



REGISTERED OFFICE

1007-1008, DEV ATELIER COMPLEX, NR. SEEMA HALL, PRAHLADNAGAR ROAD, SATELLITE, AHMEDABAD - 380015, GUJARAT INDIA.

FACTORY

C-1/58 PHASE-2 GIDC ESTATE, VATVA - AHMEDABAD - 382445, GUJARAT INDIA.
 (O) +91 79 - 4008 5720 (W) www.mahavirdyes.com (E) info@mahavirdyes.com